

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A back-drivable surgical robot head comprising:
 - (a) ~~a manually-graspable driving member frame;~~
 - (b) an arm for carrying a tool the position of which is to be controlled; [[and]]
 - (c) ~~a manually-graspable driving member on said arm; and~~
[[[c]]d] a first rotation control mechanism for rotating the arm about a first an axis[[,]] with respect to said frame, said first rotation control mechanism comprising:
 - (i) a first lead screw having a rotational motor coupled at one end thereof, said lead screw and motor being mounted at said one end to pivot with respect to said frame;
 - (ii) a bearing which moves longitudinally of said first lead screw as it rotates, said bearing being coupled to an offset crank of or secured to said arm, said lead screw taking up a zero pivotal position when said bearing is at said one end of said lead screw, said lead screw pivoting away from the zero position as force is applied to said driving member causing the bearing to move along said lead screw, said lead screw pivoting away from the zero position as the bearing moves to a maximal pivotal position in which the bearing is part way along the lead screw, and returning to the zero position as the bearing reaches an extreme position at an end of the lead screw opposite said one end.

~~the first rotation control mechanism comprising a first rotational motor coupled to a first lead screw and a bearing which moves longitudinally of the first lead screw as it rotates, the bearing being pivotally coupled to an offset crank of or secured to the arm.~~
2. (Cancelled)
3. (Previously Presented) A robot head as claimed in claim 1 in which the first motor is directly secured to the first lead screw, without any intervening gears.

4. (Cancelled)
5. (Currently Amended) A robot head as claimed in claim 1 further including a first output position encoder for measuring the angular position of the arm about the [[first]] axis.
6. (Previously Presented) A robot head as claimed in claim 1 further including a first input position encoder for measuring rotation of the first motor.
7. (Currently Amended) A robot head as claimed in claim 5 in which the measurement from the first output position encoder is compared with an expected arm position based on the measurement from a ~~first input position encoder~~ safety sensor, and an alarm is raised if the expected position is inconsistent with the actual position.
8. (Previously Presented) A robot head as claimed in claim 1 further including a second rotation control mechanism for rotating the arm about a second axis, the said mechanism comprising a second rotational motor coupled to a second lead screw and a bearing which moves longitudinally of the second lead screw as it rotates, the bearing being pivotably coupled to an offset crank of or secured to the arm.
9. (Original) A robot head as claimed in claim 8 in which the second motor and the second lead screw are mounted for pivotal motion with respect to a frame of the head.
10. (Previously Presented) A robot head as claimed in claim 8 in which the second motor is directly secured to the second lead screw, without any intervening gears.
- 11-14. (Cancelled)
15. (Previously Presented) A robot head as claimed in claim 8 in which the first axis is perpendicular to the second.
16. (Previously Presented) A robot head as claimed in claim 8 in which the arm is extendible along a third axis.

17. (Previously Presented) A robot head as claimed in claim 15 in which the first, second and third axes intersect at a point.
18. (Original) A robot head as claimed in claim 16 in which the arm is extendible on a third lead screw which is rotated by a third rotational motor.
- 19-23. (Cancelled)
24. (Previously Presented) A robot head as claimed in claim 1 further comprising a force sensor for sensing forces applied to the driving member by a user.
25. (Previously Presented) A robot head as claimed in claim 24 wherein the first rotational control mechanism is arranged to rotate the arm about the first axis in response to the sensed forces.